

LIVE-VIEWER

Wireless Camera Receiver with Monitor



LIVE-VIEWER

- The LIVE-VIEWER is an integrated diversity receiver that includes the reception electronics, 2 LNB and video monitor all in a single package.
- The LNB can be exchanged to adapt to 1310-1700, 1990-2380 and 2310-2700 MHz reception bands.
- This product is particularly suited for on the field, link check and for security application, due to the high degree of integration.

Specifications

- 3 frequency bands from 1.3GHz to 2.7GHz
- Modulation DVB-T or Proprietary (DPRO)
- MPEG2 compression: 4:2:0 / 4:2:2 profiles
- PIN code for content privacy
- 8 MHz channel bandwidth
- Operating temperature range: -10°C to +50°C
- CE and UL certified (EMC and safety)
- 1 digital video output SDI
- 1 composite video output CVBS
- 1 compressed stream ASI output
- 2 balanced audio channels
- MRC Diversity reception
- DC power input (10 – 35 Vdc)
- Power consumption: 30 W (typical)
- Weight: 4,6 kg
- Size: 300 x 280 x 80mm

Options

- Reception LNBs for three standard frequency bands: 1310-1700, 1990-2380, 2310-2700 MHz
- DPRO8 option: improved DVB-T system, especially suited for mobile applications

Applications

- On the field signal monitoring
- Mobile reception
- Security applications

Reference

Vehicular reception during Tour de France.